

Rezolutie senzor	2MP
Rezolutie inregistrare	1920 x 1080 / 1-30 fps
LUX	Color: 0.1Lux @(F1.2,AGC ON); 0 Lux cu IR, Alb/Negru 0.01 Lux @ (F1.2,AGC ON),0 Lux cu IR
Compresie video	H.265
Compresie audio	AMR/G.711A
Lentila / Zoom	2.8-12mm / 5X Zoom Optic
Ethernet	10/100 Mbps RJ45
Retea GSM	4G GSM Nano SIM Frecventa 900/1800 MHz
LED-uri IR	4 buc. vizualizare nocturna pana la 20 m
LED-uri albe	4 buc. pentru iluminare nocturna suplimentara
Detectie miscare	Da + Detectie silueta umana
Slot Card	Micro SD, max. 128Gb
Conexiune P2P	Da
Aplicatie dedicata	CamHi (Adroid/iOS) / HiP2P (Windows)
Tensiune alimentare	20 A / 11.1 V
Dimensiuni	192 x 70 x 70 mm
Grad de protectie	IP66
Carcasa	ABS
Temperatura lucru	-26°C ~ +80°C / ≤80%RH
Acumulator Li-Ion	
Capacitate / Voltaj	20 A / 12 V
Panou Solar	
Putere/Voltaj/Curent	60W (max) / 15V (Vmp) / 4A (Imp)
Incarcare	
Incarcator Solar	Model PWM
Incarcator 230V	12.6 V 5A dedicat pentru bateria Li-Ion